

Model Number	Capacity				Speed of Ram		Dimensions											
	Capacity tons	Bends		Variable Ram Stroke in.	Open Height in.	Approach Return in./min.	Variable Pressing Speed in./min.	Main Motor hp.	Hydraulic Oil us gal.	Weight (approx.) lbs.	Length in.	Distance Between uprights in.	Height in.	Width in.	Bed Height in.	Throat in.	Pit in.	Width Die Rail in.

PRESS BRAKES 25T - 35T

25T-4'	25	14GAx8'	3/16"x2'	0-4	12.5	110	88	22-65	5	25	2,200	48	38	75	30	30	7	0	2.38	3	
25T-6'										40	3,500	72	62								
35T-4'	35	14GAx6'	10GAx4'	5/16"x2'	0-4	12.5	117	122	20-60	8	25	3,500	48	38	78	30	30	7	0	2.38	3
35T-6'											40	4,500	72	62							

PRESS BRAKES 65T - 175T

65T-6'	65	11GAx7'	10GAx6'	5/16"x3'	0-6	15	181	197	12-36	10	105	8,500	72	54	94	46	32	8	0	2.75	5
65T-8'											105	10,000	96	78							
65T10'											170	12,500	120	102							
95T-6'	95	3/16"x6'	5/16"x5'	3/8"x4'	0-6	15	183	206	10-29	15	105	12,500	72	54	94	50	32	8	0	2.75	5
95T-8'											105	15,000	96	78							
95T10'											170	18,000	120	102							
95T-12'											170	21,000	144	126							
135T-6'	135	3/16"x9'	5/16"-5'	3/8"-5'	0-8	17	196	180	12-35	20	105	17,000	72	54	108	53	34	8	0	2.75	5
135T-8'											105	18,000	96	78							
135T-10'											170	21,000	120	102							
135T-12'											170	24,000	144	126							
135T-14'											170	29,000	168	150							
175T-8'	175	5/16"-8'	3/8"-7'	1/2"-5'	0-8	17	196	180	12-35	25	105	19,200	96	78	108	53	34	8	0	2.75	5
175T-10'											170	23,200	120	102							
175T-12'											170	28,500	144	126							
175T-14'											170	32,000	168	150							

PRESS BRAKES 250TC - 475TC

250TC-10'	250	1/4"-12'	3/8"-10'	1/2"-8'	5/8"-6'	0-8	17	192	191	8-24	25	140	30,000	120	102	120	56	34	8	0	3.75	5
250TC-12'												170	35,000	144	126					0		
250TC-14'												170	39,000	168	150					10		
250TC-16'												170	48,000	192	174					20		
350TC-10'	350	3/8"-14'	1/2"-11'	5/8"-8'	7/8"-5'	0-8	17	156	150	7-21	30	140	38,000	120	102	130	62	34	8	0	3.75	5
350TC-12'												170	43,000	144	126					0		
350TC-14'												205	48,000	168	150					22		
350TC-16'												205	54,000	192	174					32		
475TC-10'	475	3/8"-19'	1/2"-15'	5/8"-11'	3/4"-8'	0-8	17	161	162	6-17	40	140	50,000	120	100	142	68	34	8	12	3.75	5
475TC-12'												170	57,000	144	124					12		
475TC-14'												200	68,000	168	148					22		
475TC-16'												200	80,000	192	172					32		

PRESS BRAKES 575TC - 700TC

575TC-10'	575	5/8"-14'	1/2"-19'	3/4"-10'	1"-8'	0-8	17	160	147	6-19	50	140	65,000	123	100	146	68	34	8	12	4.75	5
575TC-12'												170	73,000	147	124					20		
575TC-14'												200	83,000	171	148					28		
575TC-16'												235	93,000	195	172					36		
700TC-10'	700	5/8"-17'	1/2"-23'	3/4"-12'	1"-10'	0-8	17	147	153	7-21	60	140	75,000	125	100	153	68	34	8	16	4.75	5
700TC-12'												170	82,000	149	124					28		
700TC-14'												200	90,000	173	148					36		
700TC-16'												235	97,000	197	172					40		

*All specifications & dimensions are subject to change without notice. Longer machines & greater capacity available upon request.