

		70T	110T	
		8'	10.5'	13.75'
Capacity	tons	70	113	
Bed length	in.	98	126	165
Distance between frames	in.	81	106	146
Open height	in.	19	19	
Stroke	in.	8	8	
Throat	in.	12	16	
Bed width	in.	2	2	
Approach speed	in./min.	236	236	
Max. pressing speed	in./min.	24	24	
Return speed	in./min.	283	236	
Backgauge travel	in.	20	20	
Main motor	kW/hp	7.5/10	7.5/10	
Length	in.	107	138	177
Width		61	63	
Height		99	101	
Weight	lbs.	12,100	17,600	20,900

		180T		280T	
		10.5'	13.75'	10.5'	13.75'
Capacity	tons	180		281	
Bed length	in.	126	165	126	165
Distance between frames	in.	106	146	106	146
Open height	in.	19		19	
Stroke	in.	8		8	
Throat	in.	16		16	
Bed width	in.	3		4	
Approach speed	in./min.	236		236	
Max. pressing speed	in./min.	24		24	
Return speed	in./min.	236		236	
Backgauge travel	in.	20		20	
Main motor	kW/hp	7.5/10	11/15	11/15	15/20
Length	in.	138	177	138	177
Width		65		68	
Height		103		103	
Weight	lbs.	22,000	26,400	33,000	35,200

		360T		450T		560T	
		10.5'	13.75'	13'	16.4'	13'	16.4'
Capacity	tons	360		450		563	
Bed length	in.	126	165	157	197	157	197
Distance between frames	in.	106	146	124	163	124	163
Open height	in.	19		19		22	
Stroke	in.	8		13		13	
Throat	in.	16		16		16	
Bed width	in.	5		6		12	
Approach speed	in./min.	189		189		177	
Max. pressing speed	in./min.	19		19		19	
Return speed	in./min.	201		189		189	
Backgauge travel	in.	20		20		28	
Main motor	kW/hp	15/20		37/50		45/60	
Length	in.	138	177	177	217	177	217
Width		77		79		106	
Height		105		115		207	
Weight	lbs.	46,200	48,400	59,400	70,400	83,600	99,000

		675T		900T	
		19.5'	23'	19.5'	26.25'
Capacity	tons	675		900	
Bed length	in.	236	276	236	315
Distance between frames	in.	199	238	199	244
Open height	in.	25		32	
Stroke	in.	13		16	
Throat	in.	16		20	
Bed width	in.	12		16	
Approach speed	in./min.	177		177	
Max. pressing speed	in./min.	19		19	
Return speed	in./min.	189		165	
Backgauge travel	in.	28		39	
Main motor	kW/hp	55/75		2 motors 37/50	
Length	in.	256	295	256	335
Width		118		130	
Height		231		254	
Weight	lbs.	134,200	147,400	206,800	253,000

		1,125T		1,350T	
		26.25'	39.3'	26.25'	39.3'
Capacity	tons	1,125		1,350	
Bed length	in.	315	472	315	472
Distance between frames	in.	244	356	244	356
Open height	in.	32		36	
Stroke	in.	16		16	
Throat	in.	24		24	
Bed width	in.	16		16	
Approach speed	in./min.	165		154	
Max. pressing speed	in./min.	19		17	
Return speed	in./min.	165		154	
Backgauge travel	in.	39		39	
Main motor	kW/hp	2 motors 45/60		2 motors 45/60	
Length	in.	335	492	335	492
Width		146		169	
Height		270		286	
Weight	lbs.	286,000	396,000	341,000	484,000

		1,800T		2,250T		2,800T	
		26.25'	39.3'	26.25'	39.3'	39.3'	52.2'
Capacity	tons	1,800		2,250		2,810	
Bed length	in.	315	472	315	472	472	630
Distance between frames	in.	244	356	244	356	356	512
Open height	in.	36		36		36	
Stroke	in.	16		16		16	
Throat	in.	24		24		24	
Bed width	in.	20		20		20	
Approach speed	in./min.	142		142		130	
Max. pressing speed	in./min.	17		14		12	
Return speed	in./min.	142		142		130	
Backgauge travel	in.	39		39		39	
Main motor	kW/hp	2 motors 55/75		2 motors 55/75		2 motors 55/75	
Length	in.	335	492	335	492	492	650
Width		193		217		236	
Height		354		394		413	
Weight	lbs.	418,000	572,000	572,000	704,000	880,000	990,000

*Specifications subject to change without notice, please contact us prior to purchase.