

			5/32" - 8'	5/32" - 10'	5/32" - 13'
Shearing thickness	Mild Steel	in.	0.16		
	Stainless	in.			
Cut length		in.	98	126	157
Rake angle		°	1° - 30'	1° - 30'	1° - 30'
Backgauge	Travel	in.	23' 5"	23' 5"	23' 5"
Main motor		kW/HP	5.5/7.5	5.5/7.5	5.5/7.5
Shipping dimensions	Length	in.	122	150	182
	Width		56	61	67
	Height		58	62	68
	Weight	lbs.	7,480	9,460	17,380

			1/4" - 8'	1/4" - 10'	1/4" - 13'	1/4"- 19' 6"
Shearing thickness	Mild Steel	in.	1/4	1/4	1/4	1/4
	Stainless	in.	1/8	1/8	1/8	1/8
Cut length		in.	98	126	157	236
Rake angle		°	1° - 30'	1° - 30'	1° - 30'	1° - 30'
Backgauge	Travel	in.	23' 5"	23' 5"	23' 5"	31' 5"
Main motor		kW/HP	7.5/10	7.5/10	7.5/10	11/15
Shipping dimensions	Length	in.	124	150	180	264
	Width		60	64	78	95
	Height		64	64	74	83
	Weight	lbs.	10,560	13,100	20,810	37,400

			5/16" - 8'	5/16" - 10'	5/16" - 13'	5/16" - 16'
Shearing thickness	Mild Steel	in.	0.31			
	Stainless	in.				
Cut length		in.	98	126	157	196
Rake angle		°	1° - 30'	1° - 30'	1° - 30'	1° - 30'
Backgauge	Travel	in.	23' 5"	23' 5"	23' 5"	31' 5"
Main motor		kW/HP	11/15	11/15	11/15	18.5/25
Shipping dimensions	Length	in.	123	170	180	228
	Width		66	72	78	99
	Height		68	68	74	87
	Weight	lbs.	12,760	15,950	20,810	52,800